arXiv:1202.1896v1 [cs.DM] 9 Feb 2012

THE BLACK-AND-WHITE COLORING PROBLEM ON CIRCLE GRAPHS

Ton Kloks[1]*, Sheung-Hung Poon[1], and Yue-Li Wang[2]

[1] Department of Computer Science
National Tsing Hua University
No. 101, Section 2, Kuang Fu Road, Hsinchu, Taiwan
spoon@cs.nthu.edu.tw
[2] Department of Information Management
National Taiwan University of Science and Technology
No. 43, Section 4, Kee-Lung Road, Taipei, Taiwan
ylwang@cs.ntust.edu.tw

Abstract. Given a graph G and integers b and w. The black-and-white coloring problem asks if there exist disjoint sets of vertices B and W with $|B| = b$ and $|W| = w$ such that no two vertices $x \in B$ and $y \in W$ are adjacent. In this paper we show that the problem is polynomial when restricted to permutation graphs and, more generally, to circle graphs.

1 Introduction

Definition 1. *Let $G = (V, E)$ be a graph and let b and w be two integers. A black-and-white coloring of G colors b vertices black and w vertices white such that no black vertex is adjacent to any white vertex.*

In other words, the black-and-white coloring problem asks for a complete bipartite subgraph M in the complement $\bar{G}$ of G with b and w vertices in the two color classes of M.

The black-and-white coloring problem is NP-complete for graphs in general [11]. That paper also shows that the problem can be solved for trees in $O(n^3)$ time. In a recent paper the timebound for an algorithm on trees was improved to $O(n^2 \log^3 n)$ time [4]. The paper [4] mentions, among other things, a manuscript by Kobler, *et al.*, which shows that the problem can be solved in polynomial time for graphs of bounded treewidth.

In a recent paper [12] we examined the black-and-white coloring problem on some other classes of graphs. We showed that the problem is polynomial for distance-hereditary graphs and for strongly chordal graphs. Furthermore, we showed that the problem remains NP-complete on splitgraphs.

* National Science Council of Taiwan Support Grant NSC 99–2218–E–007–016.

In this paper we investigate the complexity of the problem for permutation graphs and for circle graphs. We introduce permutation graphs here and we describe the algorithm for this class of graph in the next section. In Section 3 we describe the algorithm for the class of circle graphs.

An intersection model for permutation graphs is obtained as follows. Consider two horizontal lines L_1 and L_2, one above the other. Label n distinct points on L_1 and on L_2 with labels $\{1,\ldots,n\}$. For each $k \in \{1,\ldots,n\}$ connect the point with label k on L_1 with the point with label k on L_2 by a straight line segment. This is called a permutation diagram. The corresponding permutation graph with vertices $\{1,\ldots,n\}$ is the intersection graph of the line segments.




Fig. 1. A permutation graph and its permutation diagram

Permutation graphs are exactly those comparability graphs for which the complement is also a comparability graph. Permutation graphs can be recognized in linear time [17]. A permutation diagram can be obtained in linear time.

2 Black-and-white colorings of permutation graphs

Definition 2. *Consider a permutation diagram of a permutation graph* G. *A scanline is a linesegment* ℓ *that connects a point on* L_1 *with a point on* L_2*, such that the endpoints of* ℓ *do not coincide with the endpoints of any line segment that represents a vertex of* G.

A black-and-white coloring with b black vertices and w white vertices is optimal if every uncolored vertex has a black and a white neighbor.

Lemma 1. *Assume there exists an optimal black-and-white coloring of* G *with* b *black vertices and* w *white vertices. Then there exists a collection of pairwise non-intersecting scanlines such that the vertices which are uncolored are exactly the line segments that cross one or more scanlines.*

Proof. Remove the line segments from the diagram of the vertices that are not colored. Each of the remaining components is colored uniformly black or white. Notice that the components form a linear sequence of connected parts in the diagram. Place a scanline between any two consecutive components. The vertices that are not colored, *i.e.*, those that have been removed from the diagram, are precisely those that cross one or more of the scanlines. □

Theorem 1. *There exists a polynomial-time algorithm which checks if a permutation graph can be colored with* b *black and* w *white vertices.*

Proof. Consider a permutation diagram for a permutation graph $G = (V, E)$. Define a piece as a pair of non-intersecting scanlines.

Consider the subgraph of G induced by the line segments with both endpoints between the two scanlines of a piece. We identify the piece with this induced subgraph of G. Using dynamic programming, the algorithm checks if there is a black and white coloring of the piece with b' black and w' white vertices, for all values b' and w'. We describe the procedure below.

The smallest pieces consist of two scanlines such that there is exactly one line segment between them. The subgraph induced by this piece has one vertex. There are two possible optimal colorings; either the vertex is black or it is white.

Consider an arbitrary piece P, say that it consists of the scanlines s_1 and s_2. Two obvious colorings of P color all the vertices of P uniformly black or uniformly white.

Now, cut the piece P in two smaller pieces P_1 and P_2 by a scanline s which is between s_1 and s_2. Let S be the set of line segments that cross s. Consider colorings of P where the vertices of S remain uncolored.

If there are colorings with b_1 and w_1 vertices colored black and white in P_1 and with b_2 and w_2 black and white vertices in P_2, then P can be colored with $b_1 + b_2$ black vertices and $w_1 + w_2$ white vertices. In this manner, by varying s over all possible scanlines that are between s_1 and s_2, we obtain a table of all the possible colorings of the piece P.

There are $O(n^4)$ different pieces, namely, there are $O(n^2)$ scanlines, and each piece is bordered by two of them. To process a piece, we try $O(n^2)$ scanlines that are between the two bordering scanlines. By table look-up, the algorithm checks if there is a black-and-white coloring of the piece with b' black vertices and w' white vertices. Each table consists of $O(n^2)$ entries. Therefore, a table for the piece can be computed in $O(n^8)$ time.

This proves the theorem. □

Remark 1. It is easy to improve upon the timebound that is mentioned in the proof of Theorem 1. To maintain the clarity of the exposition we omit the details.

3 Black-and-white colorings of circle graphs

Definition 3. *A graph is a circle graph if it is the intersection graph of chords in a circle.*

The class of circle graphs contains many other classes of graphs such as distance-hereditary graphs and outerplanar graphs. Notice that also permutation graphs are circle graphs. It is easy to see that permutation graphs are those circle graphs that have a circle diagram with an equator, that is, an additional chord which crosses every other chord.

It is easy to see that the class of circle graphs is closed under local complementations [6]. Bouchet shows that a graph is a circle graph if and only if it has no vertex-minor isomorphic to W_5, W_7 or BW_3 [7] (see also [9]). Bouchet gives an $O(n^5)$ recognition algorithm. There are two $O(n^3)$ recognition algorithms, one by Naji [14] and the other by Gabor, Hsu and Supowit [8]. As far as we know, Spinrad's algorithm, which runs in $O(n^2)$ time is the fastest, so far [16]. An 'almost' linear-time recognition algorithm was announced in [10].

In this section we show that the black-and-white coloring problem is polynomial for the class of circle graphs.

Consider a circle graph diagram for a circle graph $G = (V, E)$. A scanline is a chord in the circle whose endpoints do not coincide with the endpoints of the chords that represent the vertices of the graph. A scanline s corresponds to a separator S in the graph, consisting of those vertices in G whose chords cross s. As in the previous section, it is easy to see that the black-and-white coloring problem reduces to finding a collection of noncrossing scanlines.

Theorem 2. *There exists a polynomial time algorithm which checks if a circle graph can be colored with* b *black and* w *white vertices.*

Proof. Let $G = (V, E)$ be a circle graph and consider a circle diagram for G. Let C denote the circle of this diagram. Consider a scanline s with endpoints t and b on C. Let C' be the part of the circle when traversing it from t to b in clockwise order. Consider the subgraph G' induced by the chords whose endpoints are on C'. We describe a dynamic programming algorithm which checks if G' has a coloring with b black vertices and w white vertices.

Define two partial orders on pairs of noncrossing scanlines with both endpoints on C' as follows. Let s_1 and s_2 be two of these scanlines. Define $s_1 \prec_1 s_2$ if the part C' that has the endpoints of s_1 is properly contained in the part of C' that has the endpoints of s_2. Thus, for each scanline s' of C' we have that $s' \prec_1 s$. We refer to this partial order as the containment order.

The second partial order is defined as follows. Let s_1 and s_2 be two noncrossing scanlines with endpoints on C'. Define $s_1 \prec_2 s_2$ if one encounters both endpoints

of s_1 before the two endpoints of s_2, when one traverses C' in clockwise order from t to b. We refer to this partial order as the circular order.

With each scanline s' we identify the subgraph S' of G induced by the following set of chords. Let $C(s')$ be the part of C' with the endpoints of s'. Then S' is the subgraph induced by the chords with both ends in $C(s')$.

We assume that for each s' for which S' is a proper induced subgraph of G', a table has been computed. This table contains the information whether there is a black-and-white coloring of S' with b black vertices and w white vertices. To process the piece S the algorithm computes new tables for the scanlines s' with both ends in C'. We describe the precise contents of these tables below.

Let s' be a scanline with both ends in C'. We may assume that S' contains at least one vertex. Consider a chain of scanlines Δ in the $\prec_2$-order with maximal element s'. Let R be the set of vertices in G', of which the chords do not cross any scanline of Δ, and that are not contained in any S'' for $s'' \in \Delta$. Thus R is the area bounded by s and the scanlines of Δ. We consider colorings of G' such that all vertices of R are colored black.

We need to maintain the number of elements of R without tabling every possible chain Δ. The important observation is that each chord that crosses s' crosses at most one other scanline of Δ.

For each successor $\bar{s}$ of s', we keep a variable which indicates the number of chords that cross $\bar{s}$ and some element of Δ.

To summarize, the table of a scanline s' contains the following information. Each row in the table characterizes a coloring of S as follows.

(a) Values b and w which indicate the number of black and white vertices in the coloring.
(b) A scanline s' which indicates the maximal element of some chain Δ in the $\prec_2$ order.
(c) A number r which indicates the number of vertices in R. Here, R is the set of vertices in G' of which the chord are not in any S'' for $s'' \in \Delta$ and which do not cross any scanline of Δ. In other words, R is the 'area' bounded by s and the chords of Δ. All the vertices of R are colored black.
(d) For each successor $\bar{s}$ of s' in the $\prec_2$ order, the number of chords that cross $\bar{s}$ and some element of Δ.

Notice that a table for a successor $\bar{s}$ of s' in the $\prec_2$ order can be computed in polynomial time. We restrain from analyzing the size of the table. Although of polynomial size it is rather large.

The algorithm sorts all pieces S (with scanline s) in order of non-decreasing size. A table for each piece can be computed in polynomial time from the tables of the smaller pieces. Finally, to see if there is a coloring of G with b black and w white vertices, the algorithm checks all scanlines s, and combines colorings of the two pieces incident with s.

This proves the theorem. □

References

1. Berend, D., E. Korach and S. Zucker, Two-anticoloring of planar and related graphs, *Proceedings of the International Conference on Analysis of Algorithms*, DMTCS Conference Volume AD (2005), pp. 335–342.
2. Berend, D., E. Korach and S. Zucker, A reduction of the anticoloring problem to connected graphs, *Electronic Notes in Discrete Mathematics* **28** (2007), pp. 445–451.
3. Berend, D., E. Korach and S. Zucker, Anticoloring and separation of graphs, *Discrete Mathematics* **310** (2010), pp. 390–399.
4. Berend, D. and S. Zucker, The black-and-white coloring problem on trees, *Journal of Graph Algorithms and Applications* **13** (2009), pp. 133–152.
5. Bodlaender, H., T. Kloks, D. Kratsch and H. Müller, Treewidth and minimum fill-in on d-trapezoid graphs, *Journal of Graph Algorithms and Applications* **2** (1998), pp. 1–20.
6. Bouchet, A., Reducing prime graphs and recognizing circle graphs, *Combinatorica* **7** (1987), pp. 243–254.
7. Bouchet, A., Circle graph obstructions, *Journal of Combinatorial Theory, Series B* **60** (1994), pp. 107–144.
8. Gabor, C., W. Hsu and K. Supowit, Recognizing circle graphs in polynomial time, *Journal of the ACM* **36** (1989), pp. 435–474.
9. Gasse, E., A proof of a circle graph characterization, Note in *Discrete Mathematics* **173** (1997), pp. 277–283.
10. Gioan, E., C. Paul, M. Tedder and D. Corneil, Circle graph recognition in time $O(n + m)\alpha(n + m)$. Manuscript in ArXiv: 1104.3284v2, 2011.
11. Hansen, P., A. Hertz and N. Quinodos, Splitting trees, *Discrete Mathematics* **165** (1997), pp. 403–419.
12. Kloks, T., S. Poon, F. Tsai and Y. Wang, The black-and-white coloring problem on distance-hereditary graphs and strongly chordal graphs. Manuscript 2012.
13. Kratsch, D., T. Kloks and H. Müller, Measuring the vulnerability for classes of intersection graphs, *Discrete Applied Mathematics* **77** (1997), pp. 259–270.
14. Naji, W., Reconnaissance des graphes de cordes, *Discrete Mathematics* **54** (1985), pp. 329–337.
15. Pnueli, A., A. Lempel and S. Even, Transitive orientation of graphs and identification of permutation graphs, *Canadian Journal of Mathematics* **23** (1971), pp. 160–175.
16. Spinrad, J., Recognition of circle graphs, *Journal of Algorithms* **16** (1994), pp. 264–282.
17. Tedder, M., D. Corneil, M. Habib and C. Paul, Simpler linear-time modular decomposition via recursive factorizing permutations, *Proceedings ICALP 08*, Springer-Verlag LNCS 5125 (2008), pp. 634–645.